



euro  gine  
Technology for Women's Healthcare

ANCORA® 375 Ag

# IUD ANCORA<sup>®</sup>

## 375 Ag

Référence  
426745

### DESCRIPTION

Intra-uterine device, with a "Ω" shaped structure, a 375 mm<sup>2</sup> copper wire and a silver core.

Intra-uterine contraception. Sterile. Product for single use.

EC mark, non-active implantable device in accordance with Directive 93/42/EEC Class III.

TECHNICAL FUNCTIONS					
COMPONENT	COMPOSITION	DIMENSIONS			
IUD structure	Polyethylen + Barium Sulfate	Ref. 426745	Size Normal	Width 20 mm	Length 35 mm
Wire	Copper purity 99,99%	Diam. 0.40 mm	Length 298 mm	Area 375 mm <sup>2</sup>	Diam. Silver Core 0.10 mm
Withdrawal wire	Polyethylen	Diam. 0.25 mm		Length 280 mm x 2	
Insertion tube	Polyethylen	External Diam. 3.80 mm		Length 195 mm	
Top gauge size	Polypropylen	Width 7.80 mm	Length 12.50 mm	Height 6.25 mm	
STERILISATION METHOD			INSERTION SYSTEM		
Ethylen Oxide			Push the IUD through the cervical canal into the cavity of the uterus.		
PRESENTATION		MAXIMUM DURATION "IN SITU"			
1 x 1 packaging		5 years			

Rev. 04-2021

Mantographic.be



More for Less...

