



euro²gine
Technology for Women's Healthcare

IUD NOVAPLUS® T 380 Ag

Références

4267381 / 4267407 / 467399

DESCRIPTION

Intra-uterine device, with a "Y" shaped structure. Can be placed in the insertion tube by pulling the wires.

Copper surface of 380 mm², with a silver core.

Intra-uterine contraception. Sterile. Product for single use.

EC mark, non-active implantable device in accordance with Directive 93/42/EEC Class III.



More for Less...



TECHNICAL FUNCTIONS

COMPONENT	COMPOSITION	DIMENSIONS			
IUD structure	Polyethylen + Barium Sulfate	Ref. 4267381 4267407 4267399	Size Normal Mini Maxi	Width 31 mm 24 mm 36.50 mm	Length 33 mm 30.50 mm 38 mm
Wire	Copper purity 99,99%	Diam. 0.40 mm	Length 302 mm	Area 380 mm ²	Diam. Silver Core 0.10 mm
Withdrawal wire	Polyethylen	Diam. 0.25 mm		Length 280 mm x 2	
The Stem	Polyethylen	Diam. 2.20 mm		Length of use 200 mm	
Insertion tube	Polyethylen	External Diam. 3.80 mm		Length 195 mm	
Top gauge size	Polypropylen	Width 7.80 mm	Length 12.50 mm		Height 6.25 mm

STERILISATION METHOD

Ethylen Oxide

INSERTION SYSTEM

Push the IUD with the stem of the insertion tube into the cavity of the uterus.

PRESENTATION

1 x 1 packaging

MAXIMUM DURATION "IN SITU"

5 years